according to 1907/2006/EC

Printing date 26.06.2023

Revision: 26.06.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SEALING GEL

UFI: 6F00-W0FC-D008-4SP8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture Sealant

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Prefa Aluminiumprodukte GmbH Werkstraße 1 3182 Marktl/Lilienfeld Austria T: +43 2762 502 0 Email: office.at@prefa.com

Further information obtainable from:

External: Dick Sundström E-mail: d.s@sunco.se

1.4 Emergency telephone number:

+43 2762 502 0 Available during office hours: Monday - Thursday: 07:00 - 12.00, 13:00 - 17:00 h Friday: 07:00 - 13:00 h

National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H336 May cause drowsiness or dizziness.

Additional information: For the wording of the hazard categories, see section 16.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



according to 1907/2006/EC

Printing date 26.06.2023

Version number 1.1 (replaces version 1.0)

Revision: 26.06.2023

Trade name: SEALING GEL

(Contd. of page 1)





Signal word Warning

Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P233	Keep container tightly closed.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves / protective clothing.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with
	water or shower.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
A .1.1141	

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: The mixture does not contain PBT substances $\ge 0,1$ %.

vPvB: The mixture does not contain vPvB substances $\ge 0,1$ %.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

[% (w/w)]

CAS: 64742-48-9 EC number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	25 – 50%
Index number: 649-327-00-6 Reg.nr.: 01-2119463258-33-XXXX	 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066 	
	(Cor	itd. on page 3)

according to 1907/2006/EC

Printing date 26.06.2023

Version number 1.1 (replaces version 1.0)

Revision: 26.06.2023

Trade name: SEALING GEL

(Contd. of page 2)

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In case of discomfort or doubt, seek medical advice.

If unconscious, use a stable lateral position and do not administer anything through mouth.

Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Wash with plenty of soap and water.

Take off contaminated clothing and wash it before reuse.

Seek medical treatment in case of complaints.

After eye contact:

Rinse opened eye for several minutes under running water.

Remove contact lenses, if present and easy to do. Continue rinsing.

Seek medical treatment in case of complaints.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do NOT induce vomiting.

Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Depending on the condition of the patients, the doctor must assess the symptoms and the overall general condition.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

COx

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Do not inhale explosion gases or combustion gases.

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

(Contd. on page 4)

according to 1907/2006/EC

Printing date 26.06.2023



Page 4/12

Version number 1.1 (replaces version 1.0)

Revision: 26.06.2023

Trade name: SEALING GEL

(Contd. of page 3)

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Restricted access to the affected area until cleaning work is completed.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Do not breathe vapour/spray.

Keep away from ignition sources.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding, inert material (sand, diatomite, acid binders, universal binders).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Keep receptacles tightly sealed.

Avoid contact with skin and eyes.

Prevent formation of aerosols.

Avoid breathing mist/vapours/spray.

Use personal protective equipment as required.

Observe protective measures and safety instructions.

Information about fire - and explosion protection:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a dry, cool, well-ventilated area.

Store in accordance with local/regional/national/international regulations.

Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with acids.

Do not store together with alkalis (caustic solutions).

Store away from oxidising agents.

according to 1907/2006/EC

Printing date 26.06.2023

Version number 1.1 (replaces version 1.0)

Revision: 26.06.2023

Page 5/12

Trade name: SEALING GEL

(Contd. of page 4)

Further information about storage conditions:
Keep container tightly sealed.
Store only in the original receptacle.
Protect from heat and direct sunlight.
Recommended storage temperature: room temperature

Storage class: 3

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELS		
CAS: 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics		
Oral	Long-term exposure - systemic effects	46 mg/kg bw/d (consumer)
Dermal	Long-term exposure - systemic effects	46 mg/kg bw/d (consumer)
		77 mg/kg bw/d (workers)
Inhalative	Long-term exposure - systemic effects	185 mg/m³ (consumer)
		871 mg/m³ (workers)

PNECs No data available.

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls

No further data; see section 7.

Technical measures and the use of suitable working methods take priority over the use of personal protective equipment.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Do not eat or drink while working.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing.

Do not inhale gases / fumes / aerosols.

Ensure good ventilation/exhaustion at the workplace.

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

(Contd. on page 6)



according to 1907/2006/EC

Printing date 26.06.2023

Version number 1.1 (replaces version 1.0)

Revision: 26.06.2023

Trade name: SEALING GEL

(Contd. of page 5)

Filter A/P2 Hand protection



Protective gloves

EN 374

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Material of gloves

Material recommendation:

Nitrile rubber, NBR

Chloroprene rubber, CR

Recommended: Protection index 6, corresponding to > 480 minutes permeation time according to EN 374 Material thickness: $\ge 0.2 - 0.4$ mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

EN 166 Body protection: Protective work clothing Environmental exposure controls Do not allow to enter sewers/ surface or ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical	properties	
General Information		
Physical state	Fluid	
Colour:	Colourless	
Odour:	kerosene	
Odour threshold:	No information available.	
Melting point/freezing point:	No information available.	
Boiling point or initial boiling point and boiling		
range	160 °C	
		(Contd on page

(Contd. on page 7)

according to 1907/2006/EC

Printing date 26.06.2023



Page 7/12

Version number 1.1 (replaces version 1.0)

Revision: 26.06.2023

Trade name: SEALING GEL

	(Contd. of page 6)
Flammability	Flammable.
Lower and upper explosion limit	
Lower:	\geq 0.6 Vol % (CAS: 64742-48-9 Hydrocarbons, C9-C11,
	n-alkanes, isoalkanes, cyclics, <2% aromatics)
Upper:	\leq 7 Vol % (CAS: 64742-48-9 Hydrocarbons, C9-C11,
	n-alkanes, isoalkanes, cyclics, <2% aromatics)
Flash point:	41 °C
Auto-ignition temperature:	\geq 240 °C (CAS: 64742-48-9 Hydrocarbons, C9-C11, n-
	alkanes, isoalkanes, cyclics, <2% aromatics)
Decomposition temperature:	No information available.
рН	Not determined.
Viscosity:	
Kinematic viscosity	> 40 mm²/s
Dynamic:	No information available.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	≤ 1 hPa (CAS: 64742-48-9 Hydrocarbons, C9-C11, n-
	alkanes, isoalkanes, cyclics, <2% aromatics)
Density and/or relative density	
Density:	No information available.
Vapour density	No information available.
9.2 Other information	
Appearance:	
Form:	Pasty
Important information on protection of healt	n
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Change in condition	
Softening point/range	
Oxidising properties	No information available.
Evaporation rate	No information available.
Information with regard to physical hazar	d
classes	
Explosives	void
Flammable gases	void
Aerosols	void
Oxidising gases	void
Gases under pressure	void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	void
Self-reactive substances and mixtures	void
	(Contd. on page 8)

according to 1907/2006/EC

Printing date 26.06.2023

Version number 1.1 (replaces version 1.0)

Revision: 26.06.2023

Trade name: SEALING GEL

		(Contd. of page 7)
Pyrophoric liquids	void	
Pyrophoric solids	void	
Self-heating substances and mixtures	void	
Substances and mixtures, which emit flam	mable	
gases in contact with water	void	
Oxidising liquids	void	
Oxidising solids	void	
Organic peroxides	void	
Corrosive to metals	void	
Desensitised explosives	void	

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials:

Acids, alkalis

oxidizing agent

10.6 Hazardous decomposition products:

No decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

CAS: 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	LD50	> 5,000 mg/kg (rat)
Dermal	LD50	> 5,000 mg/kg (Rabbit)
Inhalative	LC50/4 h	> 5 mg/l (rat)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

according to 1907/2006/EC

Printing date 26.06.2023

Revision: 26.06.2023

Trade name: SEALING GEL

(Contd. of page 8)

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

LL0 (96 h) 100 mg/l (fish) (Onchorhynchus mykiss)

LL50 (48 h) > 1,000 mg/l (daphnia) (Daphnia magna)

LL50 (96 h) > 1,000 mg/l (fish) (Onchorhynchus mykiss)

12.2 Persistence and degradability

64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics 80 % (28 d)

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: The mixture does not contain PBT substances $\geq 0,1$ %.

vPvB: The mixture does not contain vPvB substances \geq 0,1 %.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Only dispose of product residues via authorised companies according to local legislation.

European waste catalogue

Notes: The European Waste Catalogue (EWC) classifies waste materials and categorises them according to what they are and how they were produced. This may cause other classifications. The final decision belongs to the last user.

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
HP3	Flammable
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

(Contd. on page 10)

according to 1907/2006/EC

Printing date 26.06.2023

Version number 1.1 (replaces version 1.0)

Revision: 26.06.2023

Page 10/12

Trade name: SEALING GEL

(Contd. of page 9)

Uncleaned packaging: **Recommendation:**

Dispose of packaging according to regulations on the disposal of packagings. Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN IMDG, IATA 14.2 UN proper shipping name ADR/RID/ADN IMDG, IATA

The mixture is exempted according to 2.2.3.1.5.1 ADR. not regulated UN1993 not regulated

FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics)

14.3 Transport hazard class(es)

ADR/RID/ADN, ADN Class

not regulated





Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR/RID/ADN	not regulated
IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
14.7 Maritime transport in bulk according to IM	0
instruments	Not applicable.
Transport/Additional information:	
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
	(Contd. on page 11)
	E



according to 1907/2006/EC

Printing date 26.06.2023

Version number 1.1 (replaces version 1.0)

Revision: 26.06.2023

(Contd. of page 10)

Trade name: SEALING GEL

UN "Model Regulation":

not regulated

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed. **Seveso category** P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Information about limitation of use: Employment restrictions concerning juveniles must be observed. **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 12)

according to 1907/2006/EC

Printing date 26.06.2023

Version number 1.1 (replaces version 1.0)

Revision: 26.06.2023

(Contd. of page 11)

Trade name: SEALING GEL

Training hints

Before handling, storage or use for the first time, employees must be informed about the properties of the substance and about measures taken to ensure safety and environmental protection.

Flammable liquids	On basis of test data
	The classification of the mixture is generally based on th calculation method using substance data according t Regulation (EC) No 1272/2008.
Department issuing SDS:	
UmEnA GmbH	
http://umena.at	
Email: office@umena.at	
Date of previous version: 28.07.2022	
Version number of previous version: 1.0	
Abbreviations and acronyms:	
ADR: Accord relatif au transport international des march International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and La EINECS: European Inventory of Existing Commercial Chen ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent	nical Substances

PREFA